

DIE BONDER

T-3000-PRO

NEW

The **T-3000-PRO** series is Tresky's most flexible die bonding platform. The systems can run all basic functions as well as the industries most advanced applications by adding a wide range of available options. As with all of Tresky's products, the PRO incorporates True Vertical Technology™ which guarantees parallelism between chip and substrate at any bond height. Together with superior ergonomics the PRO platform is the industry's most sophisticated system in its class and with the new PC software even easier to operate.

MICRO ASSEMBLY

T-3000-PRO

True Vertical Technology™

Ultra precise bond-height control

Full PC-Control



TRESKY

Dr. TRESKY AG
Switzerland
tresky@tresky.com
www.tresky.com

Advanced multi functional Die Bonder with superior ergonomic design and programmable, high accuracy Z-Drive and bonding force control.

APPLICATIONS

Die Attach, Die Sorting, Flip-Chip, 3D Packaging, MEMS, MOEMS, VCSEL, Photonics, Ultrasonic, Thermosonic, RFID, Sensor Assembly, Adhesive Bonding, UV Curing, Eutectic Bonding (AuAu, AuSn,),

FEATURES AND OPTIONS

- 
- Z-Drive with Bonding Force Control
 - TRUE VERTICAL TECHNOLOGY™
Z-movement 95mm
with 360° Tool rotation;
Dispenser, Stamping,
Ultrasonic, Scrub, Tool
Heating, Pre Form, ...
 - Flip-Chip Ultra
Beam Splitter with
multi point alignment
» 1µm placement
accuracy
 - Interface for all ▪
bonding parameter,
temperature profile
and video imaging of
Beam Splitter Optics,
Process Inspection
Camera
 - XY placement stage supporting: ▪
Waffle/Gel - Pack -, Substrate -
Holder, various Heating Plates

TECHNICAL DATA

XY- Movement (placement stage):	220mm x 220mm (manual)
Z- Movement:	95mm (automatic)
Spindle Rotation:	360°
Bond Force (standard range):	20g - 400g (other force ranges available)
Bond Force (repeatability):	±1g
Z-Measurement resolution:	±0.001mm
Max. PC Board-/ Substrate Size:	400mm x 280mm
Placement accuracy:	±10µm; ±1µm optional (process depending)
Connections:	Compressed air 5 - 6 bar / Vacuum 0.6 bar (abs)
Dimensions:	900mm x 800mm x 700mm
Weight:	85kg
Voltage:	110V / 220V

Note: All specifications are subject to change without notice

Represented by

Headquarters

www.tresky.com

Dr. TRESKY AG
Boenrainstr. 13
CH-8800 Thalwil
Switzerland
Tel.: +41 44 772 1941
tresky@tresky.com

TRESKY Corporation
704 Ginesi Drive, Suite 11A
Morganville, NJ 07751
USA
Tel.: +1 732 536 8600
sales@tresky.com

